Characterizing Risk

Michael J. Lewis

Chevron

INTRODUCTION

Managing risk is the main objective of any information security program. Risk management is composed to two primary components: risk assessment, a process of identifying threats and understanding impacts if certain events were to occur and risk mitigation, applying controls to reduce risk to tolerable levels. [1]

The importance of risk management is clear but the understanding of “risk” itself is not. Many security professionals, when asked what risk is, are likely to spout items such as process control, joint ventures, mobile devices, and social media which management likely considers as “business opportunities”. This difference of perception can inhibit funding of projects to address risk issues.

There are kernels of truth within the views of both management and security; the listed items are business opportunities but with inherently risky aspects which must be addressed by information security architecture and strategy. A uniform means for characterizing risk is needed to help one to understand how threat events may occur and allowing the design and implementation of controls to manage the risk. Chevron does this by breaking the risk themes into risks and vulnerabilities, using threat modeling and attack graphs to create plausible risk realization scenarios, and then applying controls to mitigate the risk.

RISK AND VULNERABILITIES

The initial step in Chevron’s risk characterization process is parse a risk theme into its component “risks” and “vulnerabilities”. “Risk” is defined as an element with a likelihood of causing a financial impact to the company. Chevron has identified seven “risks”: denial of service (loss of availability), data exposure (loss of confidentiality), data integrity compromise (loss of integrity), loss of physical device, health, safety, or environment incident, brand damage, and legal liability. “Vulnerabilities” are actions/elements which could lead toward realization of a risk. This definition includes traditional items (like unpatched servers) as well as other malicious (phishing Email) and non-malicious (posting information in a social networking site) activity. The key is to recognize that while individual vulnerabilities may by themselves not be dangerous, vulnerabilities strung together within a particular context can result in the realization of one of the risks. One can continue to string vulnerabilities together until reaching a risk incident.

THREAT MODELING

One way to build risk scenarios is the use of a threat modeling paradigm originally devised by Carnegie Mellon University and Sandia National Laboratories. [2] The technique is to independently brainstorm attackers, tradecraft, vulnerabilities, actions, targets, results, and objectives and completing a matrix. Threat scenarios are derived by selecting elements from each column and stringing them together. Trying all permutations of the matrix, one can develop a taxonomy of possible attacks and may identify some that otherwise escape one’s imagination. Individual attacks attack can be constructed by selecting elements from each of the columns.

Attacker	Tradecraft	Vulnerability	Action	Target	Result	Objective
Nation State	SQL Injection	Excessive Access	Spoof	Ports	Theft	Financial Gain
Hacktivist	Phishing	User Behavior	Reroute	People	Control	Strategic Advantage
Government	Malware	Zero Day	Copy	Intellectual Property	Destroy	Mayhem
Hacker	Physical Theft	Privilege Escalation	Read	Customer Data	Lawsuits	Bragging Rights
Opportunist	DDoS	Unpatched systems	Scan	Credentials	Deny	Devalue Brand
Insider	Subpoena	Insecure SDLC	Flood		Brand Damage	Damage Economy
Organized Crime	Password Cracking	SYN Floods				Industrial Espionage

Copyright is held by Chevron Corporation

CSIRHW '12, Oct 30 - Nov 01 2012, Oak Ridge, TN, USA ACM 978-1-4503-1687-3/12/10

ATTACK GRAPHS

The threat matrix is an excellent means for generating possible attacks but is somewhat cumbersome to use as minor changes (perhaps in the attacker) will generate entirely new attacks. A better means to combine multiple slightly changing attacks into graphs to provide an overall picture of the total threat.

Grouping vulnerabilities, building and documenting scenarios in this manner allows one to see that there are four basic triggers of loss: denial of service, human/process errors, loss of physical devices, and machine compromise events. Additional events may occur at a third party which could result in Chevron data (at that location) or Chevron credentials (supplied to the third party) being compromised.

The attack graphs facilitate determining where to apply security controls to address the risk. Preventive controls inserted anywhere within the string can disrupt the attack and prevent the lost. Detective and containment controls may be applied to manage attacks which evade preventive controls. The shape of the controls has significance as octagons represent preventive controls while magnifying glasses and boxes represent detection and containment measures.

RISK ASSESSMENT

A risk assessment should be executed to identify the effectiveness of the control infrastructure and the potential for damage to the company. Each path through the risk scenario may need to be assessed; consequently, each graph is likely to generate multiple assessments.

Chevron has both qualitative and quantitative risk assessment tools available. The qualitative process translates likelihood (which takes into account control effectiveness) and impact estimates into an assessment of risk as high (needing immediate short term mitigation), medium (long term mitigation) or low (optional or no mitigation). The quantitative tool takes similar information and through use of Monte Carlo simulation, calculates an annual loss exposure in dollars.

These assessments help identify places where controls are either non-existent or ineffective and to prioritize which risks to address first. These results are reflected back onto the attack graphs by the coloring of the vulnerabilities and controls. For vulnerabilities, the color coding of the boxes maps to Chevron’s risk prioritization matrix with those tending toward red of higher risk and those of green toward lower. For controls, the colors show the presence and effectiveness of the control: blue is for existing effective measures, orange for controls which exist but could be improved, and brown for new controls to be considered.

CONTROL SELECTION

If the risk is not at tolerable levels, then additional mitigations are needed. Controls selected must meet Chevron architectural principles of balancing risk and business value, making security the natural path to take, deploying a mix of prevented, detective, and containment controls as defense-in-depth, and anticipating new (future) technologies and threats. Controls may include policy, procedure, people, or technology components and often include all of these. The attack graphs are helpful in determining where controls may be placed with again the understanding that stopping/disrupting any of the vulnerabilities can disrupt the attack.

MANAGING NEW VULNERABILITIES

As the risk (items that cause impact) list is relatively static, most additional work will concern integrating new vulnerabilities into the risk scenarios. This is done by entering the new vulnerability data into the threat matrix and attack graphs. This allows one to easily “define” multiple attack paths emanating from the vulnerability.

APPLYING THE METHODOLOGY

The initial step is to document likely attack paths for a targeted attack. This allows one to understand the potential attack paths and where controls can be applied. The APT attack is initiated either by a targeted phishing attack (upper two purplish boxes) or a drive-by web browsing of a compromised site (bottom purple box). Once the initial connection is established, the perpetrator will unleash some type of malware attack that exploits some type of vulnerability in the system to gain a foothold on the device. From this perch, the attacker will then extend his/her reach by gathering authentication credentials, identifying (and infecting) other susceptible machines (as necessary), and establishing a control link back to a command server. Eventually, the attacker

The next step is to identify existing controls within the attack. There are strong preventive controls which can address the risks of unpatched vulnerabilities and known worms/viruses. Awareness training can also help address some of the risks from targeted phishing and drive-by infections.

Effective controls manage risks of specific vulnerabilities. Removing the mitigated vulnerabilities provides a diagram of residual risk. In this particular case, one can see that traditional controls effectively remove the legacy threats leaving (the imperfect) awareness training is the only remaining defense against non-legacy threats. If (or more likely when) awareness fails, there are no other controls in stream to address an attack.

The solution is to implement a set of preventive, detective, and containment controls within the Chevron network to address an APT attack that manages to elude the awareness defense. Specialized threat detection systems use various capabilities to identify and suspend nefarious activity. These solutions can address the actual zero day exploit or the internal activities that the attacker will try within the internal network. Security Incident and Event Management (SIEM) technologies cannot stop an attack but they may be able to identify one in progress. Combined with incident response/crisis management processes and virtualized browser technologies, these solutions can help contain the attack and mitigate potential damages.

Pulling it all together, we can see that with a combination of existing, new, and improved controls, we can put together a defense-in-depth architecture that can address a targeted attack.

REFERENCES

[1] These concepts of risk management are covered in more detail in “Enterprise Security Architecture: A Business Driven Approach” by John Sherwood, Andrew Clark, and David Lynas. (CMP Books, San Francisco, 2005)

[2] John Howard, Thomas Longstaff; “A Common Language for Computer Security Incidents”; Sandia National Laboratories; October 1998. DOI= http://www.cert.org/research/taxonomy_988667.pdf